

INTERLIGHT[®]

CHARGE YOUR TOMORROW



NRGT Series Batteries

220Ah to 260Ah



MEETS IEC 61427-1 SPECIFICATIONS

CHARGE
YOUR
TOMORROW

INTERLIGHT[®]



NO
INTERNAL PACKING



LOW
MAINTENANCE



FASTER
RECHARGE



SUPERIOR
VOLTAGE



PATENTED CONTAINER
287292, 287295



PARTIAL STATE OF
CHARGE CONDITION



LONGER
LIFE



INCREASED
BACK-UP

Note: Color of the product may vary from the original color in this document.

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continued improvement and we reserve the right to change details without prior notice.

Features

- Special Selenium alloy grid, casted at high pressure by pressure dye casting machine (PDC) for void free structure to provide longer life.
- 99.99% pure active material with finest quality red lead.
- Extra strong, flexible oxidation-resistant gauntlet for higher performance.
- Special Thick P.E separators are used to increase the efficiency & life.

Benefits

- Long design life
- Very low maintenance
- Can handle extreme weather conditions
- Rugged Performance
- Longer life without charging



Range available: 220Ah to 260Ah

TECHNICAL DATA

NRGT TUBULAR BATTERIES

Type of Battery	Nominal Voltage	Capacity	Dimensions mm (LxWxH)+/-3mm	Gross Battery weight+/-3% [Kg]	Battery Layout
TT220IT-NRGT	12	220	506X190X479	62	- □ □ □ □ □ +
TT240IT-NRGT	12	240	506X190X479	66	- □ □ □ □ □ +
TT260IT-NRGT	12	260	506X190X479	68	- □ □ □ □ □ +