



200Ah to 350Ah



Power That Keeps You Moving Durable, Reliable & Unstoppable

Tall Tubular Batteries For Inverter & Solar

CHARGE
YOUR
TOMORROW



NO
INTERNAL PACKING



LOW
MAINTENANCE



FASTER
RECHARGE



SUPERIOR
VOLTAGE



PATENTED CONTAINER
287292, 287295



PARTIAL STATE OF
CHARGE CONDITION



LONGER
LIFE



INCREASED
BACK-UP

MEETS IEC 61427-1 SPECIFICATIONS

Note: Color of the product may vary
from the original color in this document.

This catalogue is issued to provide outline information only
and is not deemed to form part of an offer or contract. Our policy is one of
continued improvement and we reserve the right to change details without prior notice.

Features

- Special Selenium alloy grid, casted at high pressure by pressure dye casting machine (PDC) for void free structure to provide longer life.
- 99.99% pure active material with finest quality red lead.
- Extra strong, flexible oxidation-resistant gauntlet for higher performance.
- Special Thick P.E separators are used to increase the efficiency & life.

Benefits

- Long design life
- Very low maintenance
- Can handle extreme weather conditions
- Rugged Performance
- Longer life without charging



Range available: 200Ah to 350Ah

TECHNICAL DATA

TALL TUBULAR BATTERIES

Type of Battery	Nominal Voltage	Capacity@C20 at 27°C	Dimensions mm (LxWxH)+/-3mm	Gross Battery weight+/-3% [Kg]	Battery Layout
IL200DTT	12	200	473X190X445	62	- □ □ □ □ □ +
IL250DTT	12	250	473X190X445	63	- □ □ □ □ □ +
IL350DTT	12	350	506X190X479	78	- □ □ □ □ □ +